

Claims

- [c1] 1. A plugboard for housing sockets and micro-relays, of the type used for housing a plurality of connectors, sockets or micro-relays, composed of a base (1) and a plurality of holes for housing connectors, sockets or micro-relays (2), characterized in that said holes are not aligned with each other and with the position of alternating holes for introducing the connector, socket or micro-relay rotated 180° with regard to the position of the remaining holes intended for housing the connectors, sockets or micro-relays of the ends of the plugboard.
- [c2] 2. A plugboard for housing sockets and micro-relays according to claim 1, characterized in that it is provided with three holes for housing three connectors, sockets or micro-relays, wherein the central hole intended for housing a connector, socket or micro-relay is not aligned with regard to the two holes intended for housing the connectors, sockets or micro-relays of the ends of the plugboard and with the position for introducing the connector, socket or micro-relay rotated 180° with regard to the position of the two holes intended for housing the connectors, sockets or micro-relays of the

ends of the plugboard.

- [c3] 3. A plugboard for housing sockets and micro-relays according to claims 1 and 2, characterized in that in each one of the holes of the plugboard, all the pins (3) of the connectors, sockets, or micro-relays (2) can open, ensuring the connection between plugboard and connectors, sockets or micro-relays introduced in said holes.